


GENERAL  ELECTRIC

*Airliner*


MODEL CD1-F









**Hi-speed Calrod®**—Fast and clean. No faster electric cooking unit sold. Stays clean—spills burn away. Coil length increased 49 per cent for larger heating area, extra speed.



**Master Oven**—Spacious . . . extra capacity. Hi-speed Calrod bake unit gives even-heat baking results. Open-coil Super Broiler for charcoal-type broiling. Efficient and economical.




**No-Stain Oven Vent**—Helps keep your kitchen walls and curtains shiny bright. Traps grease and moisture from oven vapors. Easy to remove . . . can be washed like a dish.




**Electric Minute Timer Clock**—Now, a handy timer right on your range. Times any cooking period from 1 to 60 minutes, accurately . . . or, for timing your laundry, too!



**Thrift Cooker**—Economical meal-planning is easy with the built-in, six-quart, aluminum Thrift Cooker. Cooks entire meal for two. More than 45 tasty dishes can be cooked on thrifty LO heat.



**Storage Drawers**—Large-capacity storage for cooking utensils right where you use them most. Three free-sliding drawers with black-japan finish. Rounded ball corners for easy cleaning. Over 3½ cu. ft. capacity.



**Time and Temperature Charts**—For quick reference while you're cooking. Handy charts give proper cooking times and temperatures for oven and surface cooking. Permanent, convenient, easy to read.



**Smooth-action Switches**—Gleaming white plastic knobs with bright-chrome trim. Smooth operation gives "jiffy-quick" switch settings. Silver contacts give extra long life, positive action. Easy to see and use.

# **GENERAL ELECTRIC**

## **SPECIFICATION FEATURES**

### **GENERAL**

Completely new functional design for maximum convenience in use and care  
 Gleaming white plastic hardware with chrome band  
 Enameled Time and Temperature charts  
 Three spacious, smooth-sliding storage drawers, black-japan finished . . . more than 3½ cu ft capacity  
 Rigid, welded, one-piece body . . . porcelain-enamel finish inside and out  
 No-Stain Oven Vent  
 Acid-resistant one-piece cooking top  
 Full-width doors and drawers  
 Counterbalanced oven door . . . ball-bearing action  
 Separate, easily replaceable fuse for appliance outlet . . . located under backplasher behind right-rear surface unit  
 Range designed for front servicing  
 Compact 39¼ inch width permits installation in minimum-size kitchen  
 Alkali-resistant toe cove

### **OVEN**

Master size for capacity  
 Rounded ball corners permit easy cleaning  
 Nontip, lock-stop, nonoxidizing, bright-finish shelves: one straight, one reversible  
 Smokeless-type, easy-to-clean broiler pan and rack . . . porcelain-enamel finish  
 Long, bar-type shelf supports integral with oven lining  
 Automatic compensated hydraulic oven thermostat . . . range 150 deg to 550 deg F  
 Broiler meter and shelf guide . . . shows the right shelf location for perfect results  
 Open-coil broiler unit  
 Calrod bake unit  
 Oven heavily insulated on all six sides . . . provides high efficiency and cool kitchens  
 Automatic preheat

### **SURFACE UNITS**

Three 5-heat, Hi-speed Calrod units  
 Hi-speed, 5-heat, open-coil Deep Well unit  
 Built-in, six-quart, aluminum Thrift Cooker  
 Aluminum reflector pans . . . removable for easy cleaning  
 Improved, thin Calrod units

Specifications subject to change without notice

\*Trade-mark Reg. U.S. Pat Off.

*Airliner*

**MODEL CD1-F**

### **CONTROL PANEL AND BACKPLASHER**

Increased height and improved styling . . . designed for added visibility and convenience  
 Electric Minute Timer Clock . . . times your cooking  
 Oven Temperature Control  
 White plastic switch knobs with bright chrome band  
 Oven Indicator Light  
 New lamp and housing . . . light where you want it  
 Convenient appliance outlet

### **UNIT EQUIPMENT**

Five-heat Calrod Surface Units  
 Two 6-inch units; 1250 watts each  
 One 8-inch unit, 2050 watts  
 Two Oven Unit  
 One Calrod bake unit, 3000 watts  
 One Open-coil broil unit, 3400/800 watts  
 Five-heat Thrift Cooker Unit  
 1250-watt open-coil unit

### **OVEN DIMENSIONS**

16 in. wide; 15 in. high; 20 in. deep with oven door closed

### **MAXIMUM CONNECTED LOAD—10.3 kw**

### **APPROXIMATE SHIPPING WEIGHT—265 lb**

Range for operation on 118/236 volts, a-c, single-phase, 3-wire service, 60 cycles. For non-standard connections, see General Electric retailer. General Electric Company, Appliance and Merchandise Department, Bridgeport 2, Conn.

PRICE: \_\_\_\_\_ DOWN PAYMENT: \_\_\_\_\_

MONTHLY PAYMENT: \_\_\_\_\_ NUMBER OF PAYMENTS: \_\_\_\_\_

